

Radon Scout PLUS



Technical Data

Measurement Range: 0 ... 10 MBq/m³

Sensitivity: 1.8 cpm @ 1000 Bq/m³ (independent on the humidity)
200 Bq/m³ with 20% statistical error (1 σ) at 1 hour interval
1000 Bq/m³ with an statistical error (1 σ) < 10 % at 1 hour interval
100 Bq/m³ with 17% statistical error (1 σ) at 3 h interval

Response Time: 120 Minutes to 95% of the final value

Internal Sensors for: Relative humidity (0 ... 100%)
Temperature (-20 ... 40°C)
Barometric pressure (800 ... 1200 mbar)
Tilt



Integration interval: 1 .. 255 Minutes adjustable by software
Storage : Non volatile, last 2047 data records
Clock: Internal real time clock
Power supply: 2 x D-size cell (NiCd, NiMH or Alkaline) and mains power
Battery operation: > 90 days
Control: single switch, measurement/stand-by (lock-function)
Display: 3 x 16 characters display with back-light
(US/SI units selectable by software)
Interface: RS232, USB
Size: 175 x 135 x 55 mm, weight 800 g (incl. Battery)

Software: Radon Vision, included

- Set-up, data download (also via modem – analogue line, ISDN, GSM)
- Interactive graphical display (zoom, pan, fit data-cursor, marker for tilt and start of a new measurement, error bars, smoothing)
- Selective ASCII export (EXCEL format)
- Selective graphical protocol print (space for individual header, user comments)
- Calculation of average concentration and exposure
- Automatic created file names and path structure
- Switch over between US and SI-units (Bq/m³/pCi/L)

The over-all content of this book is for information purposes only and therefore subject to change without notice. SARAD GmbH will not guarantee the correctness of content, expressed or implied, inside this product summary and keeps itself indemnified against all liability related to this document. © SARAD GmbH. All rights reserved.

