

# EME Guard XS 40 GHz



An EMF Monitoring Device to Alert Workers Near Antennas



- Accurate measurement with tri-axis sensors
- Instant audio and visual alarm
- Measurements up to 40 GHz

## Main features

### User profile

- Persons working near antennas including installation and maintenance workers, broadcast, PMR and mobile phone operators or regulatory body employees

### Measurement capabilities

- Continuous monitoring of Electromagnetic Field levels with isotropic tri-axis E-field sensors
- EMF Level indicated by a LED color scale
- Audio and visual alarms triggered when EMF exceeds the reference level

### Frequency bands

- 80 MHz – 40 GHz

### Safety recommendations

- ICNIRP
- FCC 96-326
- Safety Code 6
- 2013/35/UE  
*New EU Directive*
- Alarm threshold can be adjusted at MVG factory upon request

## Product Configuration

### Equipment

- EME Guard XS
- MVG Case
- Wrist strap
- Lanyard
- Connecting adapter
- Armband
- 2 x 1.5 V Size N Alkaline batteries
- Instructions for use

### Services

- Initial calibration
- Additional calibration
- Extended warranty

■ Included □ Optional

## TECHNICAL CHARACTERISTICS

Probe	Isotropic 3-axes probe
Frequency range	80 MHz - 40 GHz
Lower detection limit	5 V/m
Upper detection limit	350 V/m

## MEASUREMENT UNCERTAINTY

Frequency response	80-200 MHz : -4/-1 dB 200-1000 MHz : -2/+4 dB 1-3.5 GHz : -4/0 dB 3.5-6 GHz : 0/+6 dB 6-15 GHz : +5/+12.5 dB 15-23 GHz : -2/+7.5 dB 23-28 GHz : -6/0 dB 28-40 GHz : -4/+2 dB
Axial isotropy	100 MHz : $\pm 0.5$ dB 2.6 GHz : $\pm 1$ dB 5.5 GHz : $\pm 1$ dB

## ALARM & CONFIGURATION

Reference threshold	Alarm threshold can be adjusted at MVG factory upon request
Visual alarm	7 LEDs
Audio alarm	2 tones (activated from 5 to 350 V/m)
Low battery indicator	Orange flashing LED

## MEASUREMENT CONFIGURATION

Measurement period	1 sec
--------------------	-------

## CONDITIONS FOR USE

Temperature, humidity	-10°C to 50°C, 85% max humidity
Battery	2 x 1.5 V Size N Alkaline removable batteries
Battery life	> 1000 hours (> 50 days) <sup>(1)</sup>

## MECHANICAL CHARACTERISTICS

Dimensions	132.5 x 48.5 x 28.7 mm (LxWxH) without connecting adapter
Weight	120 g with batteries

(1) If no alarm is triggered



Contact your local sales representative for more information  
[salesteam@mvg-world.com](mailto:salesteam@mvg-world.com)  
[www.mvg-world.com/rfsafety](http://www.mvg-world.com/rfsafety)